

# A Smarter Way for Your Broadband Life

Huawei EG8120L, an intelligent bridging-type ONT

Smart service, interconnection, and O&M



## ● Device Parameters

Dimensions (L x W x H)	115 mm x 94 mm x 30 mm	System power supply	11–14 V DC, 0.5 A/1 A
Weight	about 155 g	Static power consumption	3.8 W
Operating temperature	0°C to +40°C	Maximum power consumption	4.9 W
Operating humidity	5% RH to 95% RH (non-condensing)	UNI	1GE + 1FE + 1POTS
Power adapter input	100 – 240 V AC, 50/60 Hz	Indicators	POWER/PON/LOS/LAN1/LAN2/TEL

## ● Interface Parameters

GPON Port	Ethernet Port	POTS Port
<ul style="list-style-type: none"> <li>Class B+</li> <li>Receiver sensitivity: -27dBm</li> <li>Wavelengths: US 1310 nm, DS 1490 nm</li> <li>Wavelength blocking filter (WBF)</li> <li>Flexible mapping between GEM Port and TCONT</li> <li>GPON: consistent with the SN or password authentication defined in G.984.3</li> <li>Bi-directional FEC</li> <li>SR-DBA and NSR-DBA</li> </ul>	<ul style="list-style-type: none"> <li>Ethernet port-based VLAN tags and tag removal</li> <li>1:1 VLAN, N:1 VLAN, or VLAN transparent transmission</li> <li>QinQ VLAN</li> <li>Limit on the number of learned MAC addresses</li> <li>MAC address learning</li> <li>Local switching/isolation based on Ethernet ports</li> <li>Transparent transmission of IPv6 packets at Layer 2</li> </ul>	<ul style="list-style-type: none"> <li>Maximum REN: 4</li> <li>G.711A/<math>\mu</math>, G.729a/b, and G.722 encoding/decoding</li> <li>T.30/T.38/G.711 fax mode</li> <li>DTMF</li> <li>Emergency calls (with the SIP protocol)</li> </ul>

## ● Product Function

Smart interconnection	<ul style="list-style-type: none"> <li>SIP/H.248 auto-negotiation</li> </ul>	Smart O&M	<ul style="list-style-type: none"> <li>Variable-length OMCI messages</li> <li>Active/Passive rogue ONT detection and isolation</li> <li>PPPoE/DHCP simulation testing</li> <li>Call emulation, and circuit test and loop-line test</li> </ul>
QoS	<ul style="list-style-type: none"> <li>Ethernet port rate limitation</li> <li>802.1p priority</li> <li>SP/WRR/SP+WRR</li> <li>Broadcast packet rate limitation</li> <li>Flow mapping based on the VLAN ID, port ID, or/and 802.1p</li> </ul>	Common O&M	<ul style="list-style-type: none"> <li>OMCI/Web UI</li> <li>Dual-system software backup and rollback</li> <li>802.1ag Ethernet OAM</li> <li>Optical link measurement and diagnosis</li> <li>Loopback check</li> </ul>
Security	<ul style="list-style-type: none"> <li>MAC address filtering</li> </ul>	Multicast	<ul style="list-style-type: none"> <li>IGMP v2/v3 snooping</li> <li>MLD v1/v2 snooping</li> <li>Fast leave</li> <li>VLAN tag translation, transparent transmission, and removal for downstream multicast packets</li> <li>IGMP/MLD protocol packet rate limitation</li> </ul>
Power Saving	<ul style="list-style-type: none"> <li>Indicator power saving</li> <li>Power consumption reduction of idle components in power-saving state</li> </ul>		