



8 GPON Ports

Support 1024 ONTs

V1.1.6

ITU-T G.984  
GPON ONT

2.5Gbps  
Downstream

Enhanced  
Layer 2-7  
Switching

384 T-conds  
4096 Port ID

IPv6 Ready

### SGT8000A 8 Port GPON OLT:

The SGT8000A is an ITU-T G.984.x based GPON OLT. It offers 8 GPON downstream ports that supports 1024 subscriber GPON ONTs at 1:128 Splitting Ratio. Its uplink ports support 4\*GE ports and 2\*10G SFP+ ports. The SGT8000A is IPv6 ready, It supports advanced Layer 2-7 switching features that makes it capable of applying in the most complex FTTx networks.

### Main Characters

- ITU-T G.984.x standard, interoperable with Chima and most popular GPON ONTs
- Offers 8\*GPON SC Ports, support 1024 subscriber ONTs at 1:128 Splitting Ratio
- Offers 4\*Gigabit SFP/Tx combo uplink ports and 2\*10G SFP+ uplink ports.
- Dual AC or Dual DC or 1AC+1DC Redundant Power supply
- Comprehensive GPON DBA capabilities, dynamic assignment of bandwidth
- IPv4 and IPv6 ready, suitable for applying in both IPv4 and IPv6 based Networks
- IEEE802.1Q VLAN, QinQ, VLAN translation, GVRP, highly applicable in HFC networks
- Enhanced L2-7 Switching features, support STP, RSTP, MSTP, QOS, ACL, etc.
- IGMP Snooping and Proxy for IPv4, MLD Snooping and Proxy for IPv6 multicast
- EAPS and GERP loop protection, recovering in less than 50ms
- Anti-ARP spoofing/flooding, IP Source Guard, Port Isolation, etc, enhancing security levels.
- 384 T-conds, support 5 Types of T-cont based bandwidth assignment
- 4096 Port IDs per GPON MAC, in both upstream and downstream directions
- Support OMCI, Telnet, sFlow, NMS management

## Technical Parameters

### GPON Parameters

ITU-T G.984.x GPON standard, 1310nm upstream & 1490nm downstream  
 Support G.984.1, G.984.2, G.984.3, G.984.4, G.988 GPON & OMCI protocols  
 TR-101 compliant solution for GPON OLT applications  
 1:128 Splitting Ratio, support max 1024 subscriber GPON ONTs  
 384 T-contrs, support 5 Types of T-cont bandwidth assignment  
 Max transmission distance: 20Km  
 FEC (Forward Error Correction) in upstream and downstream directions  
 SN or SN+Password methods for ONT identifier and authentication  
 T-cont bandwidth, static bandwidth and dynamic bandwidth allocation  
 4096 port-IDs per GPON MAC in upstream and downstream directions.  
 1024 allocated IDs per Gpon MAC in upstream direction  
 Fiber Transmission cable: G.652 Single mode optical fiber cable  
 Enhanced GPON debug and diagnostic functions.  
 Support NSR/SR Dynamic Bandwidth Allocation (DBA), 1Kbit/s  
 Support Forward Error Correction (FEC)  
 128bit triple churning encryption for both upstream and downstream  
 Verification of legal subscriber ONT, illegal subscriber ONT report  
 ONT Firmware upgrade: massive upgrade, timed upgrade, realtime upgrade  
 Transmission and Receiving optic power detection at PON port  
 Support Dying Gasp

### Hardware Parameters

Model NO. SGT8000A  
 Offers 8\* GPON downstream ports  
 Offers 4\*GE SFP/Tx combo upstream ports  
 Offers 2\*10G SFP+ upstream ports  
 Redundant dual AC, dual DC or 1AC+1DC power supplies:  
 AC: Input 100 ~ 240V, 47 ~ 63Hz;  
 DC: Input -36V ~ -75V;  
 Switching Capacity: 102Gbps  
 IPv4 & IPv6 Switching Througput: 75.88Mpps  
 Power consumption: ≤85W  
 Product Measurement: 440mm×44mm×380mm  
 Product Weight: ≤5kgs  
 Live Leds for all interfaces

## Layer 2 Switching Features

Layer 2 Features	MAC	MAC Black Hole Port MAC Limitation
	VLAN	IEEE802.1Q VLAN, 1-4096 VLAN IDs Port based/MAC based/IP subnet based VLAN Port-based QinQ and Selective QinQ (StackVLAN) VLAN Swap and VLAN Remark and VLAN Translate GVRP Generic VLAN registration Based on ONU service flow VLAN add, delete, replace
	Spanning Tree	IEEE 802.1D Spanning Tree Protocol (STP) IEEE 802.1w Rapid Spanning Tree Protocol (RSTP) IEEE 802.1s Multiple Spanning Tree Protocol instances (MSTP)
	Port	Bi-directional bandwidth control Static link aggregation and LACP (Link Aggregation Control Protocol) Port mirroring and traffic mirroring

Layer 2 Features	ACL	<p>Standard and extended ACL</p> <p>Time Range ACL</p> <p>Packet filter providing filtering based on source/destination MAC address, source/destination IP address, port, protocol, VLAN, VLAN range, MAC address range, or invalid frame. System supports concurrent identification at most 50 service traffic</p> <p>Support packet filtration of L2 ~ L7 even deep to 80 bytes of IP packet head</p>
	QOS	<p>Rate-limit to packet sending/receiving speed of port or self-defined flow and provide general flow monitor and two-speed tri-color monitor of self-defined flow</p> <p>Priority remark to port or self-defined flow and provide 802.1P, DSCP priority and Remark</p> <p>CAR(Committed Access Rate)、Traffic Shaping and flow statistics</p> <p>Packet mirror and redirection of interface and self-defined flow</p> <p>Super queue scheduler based on port and self-defined flow. Each port/flow supports 8 priority queues and scheduler of SP, WRR and SP+WRR.</p> <p>Congestion avoid mechanism , including Tail-Drop and WRED</p>
	IPv4 & IPv6 Multicast	<p>IGMPv1/v2/v3</p> <p>IGMPv1/v2/v3 Snooping</p> <p>IGMP Filter</p> <p>MVR and cross VLAN multicast copy</p> <p>IGMP Fast leave</p> <p>IGMP Proxy</p> <p>PIM-SM/PIM-DM/PIM-SSM</p> <p>PIM-SMv6、 PIM-DMv6、 PIM-SSMv6</p> <p>MLDv2/MLDv2 Snooping</p>
	MPLS	MPLS LDP

## Security Features

	Port Security	<p>Bi-directional bandwidth control</p> <p>Static link aggregation and LACP(Link Aggregation Control Protocol)</p> <p>Port mirroring and traffic mirroring</p>
--	---------------	--

Security Features		
	User Security	Anti-ARP-spoofing Anti-ARP-flooding IP Source Guard create IP+VLAN+MAC+Port binding Port Isolation MAC address binds to port and port MAC address filtration IEEE 802.1x and AAA/Radius authentication TACACS+ authentication dhcp anti-attack flood attack automatic suppression ONU isolation control
	OLT Security	Anti-DOS attack(such as ARP , Synflood, Smurf, ICMP attack), ARP detection, worm and Msblaster worm attack SSHv2 Secure Shell SNMP v3 encrypted management Security IP login through Telnet Hierarchical management and password protection of users
	Network Security	User-based MAC and ARP traffic examination Restrict ARP traffic of each user and force-out user with abnormal ARP traffic Dynamic ARP table-based binding Supports IP+VLAN+MAC+Port binding L2 to L7 ACL flow filtration mechanism on the 80 bytes of the head of user-defined packet Port-based broadcast/multicast suppression and auto-shutdown risk port URPF to prevent IP address counterfeit and attack DHCP Option82 and PPPoE+ upload user' s physical location Plaintext authentication of OSPF、RIPv2 and MD5 cryptograph authentication

## IP Route Features

IP Route Features	IPv4	ARP Proxy DHCP Relay DHCP Server Static route

	IPv6	ICMPv6 ICMPv6 redirection DHCPv6 ACLv6 Configured Tunnel 6to4 tunnel IPv6 and IPv4 Tunnels
--	------	--

## Reliability Features

Reliability Features	Loop Protection	EAPS and GERP (recover-time <50ms) Loopback-detection
	Link Protection	FlexLink (recover-time <50ms) RSTP/MSTP (recover-time <1s) LACP (recover-time <10ms) BFD
	OLT Protection	VRRP host backup Double fault-tolerant backup of host program and configuration files 1+1 power hot backup

## Maintenance Features

Maintenance	Network maintenance	Real-time port flow, Usage rate, Packet statistics through CLI, Telnet RFC3176 sFlow flow analysis, support Flow monitoring and statistics based on protocol or IP address LLDP Link Layer Discovery protocol Ethernet OAM Data log and RFC 3164 Syslog Support Ping and Traceroute
	Device Management	Console, Cli, Telnet and Web Management G.988 OMCI management protocol SNMP V1/V2/V3, RMON 1/2/3/9 Groups of MIB

		NTP Network Time NMS Network Management System
--	--	---

## Specification Table

Standards	IEEE 802.3, IEEE 802.3u, IEEE802.3ab, IEEE802.3z, IEEE802.3ae, IEEE 802.3x, IEEE802.1Q, IEEE802.1P, IEEE802.1D, IEEE802.1w, IEEE802.1s, ITU-T G.984.1, ITU-T G.984.2, ITU-T G.984.3, ITU-T G.984.4, ITU-T G.988, RFC3164, RFC3176		
GPON Ports	8* GPON SC Ports		
Uplink Ports	4*Gigabit SFP and 2*10G SFP+ ports		
Redundant Power Supplies	Dual DC, Dual AC or 1*AC+1*DC: AC: Input 100 ~ 240V, 47 ~ 63Hz; DC: Input -36V ~ -75V;		
Switching Capabilities	Switching Capacity: 102Gbps IPv4 & IPv6 Switching Througput: 75.88Mpps		
Power consumption	≤85W		
Ethernet Cable	10Base-Tx: UTP category 3, 4,5, up to 100m 100Base-Tx: UTP category 5, up to 100m 1000Base-Tx: UTP category 5, 5E, 6, up to 100m		
Fiber Cable	8.3μm, 8.7μm, 9μm and 10μm single mode fiber cable		
Measurement & Weight	440mm×44mm×380mm Product Weight: ≤5kgs		
Temperature & Humidity		Temperature	Humidity
	Working	0 to 50°C	10% - 90%
	Standby	-40 to 70°C	5% - 90% RH

## Order Information

Model No.	Product Description
SGT8000A	SGT8000A GPON OLT, with 8*GPON Ports, 8*1GE SFP/Tx combo uplink ports
SGTP01PWR100AC	SGT8000A AC Power Supply Module, 100W, 110-220V AC
SFP-GPON-T20	GPON SFP Transceiver, 1310Tx/1490Rx, SC/UPC, 20Km, Class B+
SGTU-10G-2-SFP+	SGT8000A Uplink Switching Board, 2*10G SFP+ slots